


5800 Series

Half Moon



General Characteristics:

Lamp Type: 2, 3, 4 or 6 Lamp T5 or T8
 Ballast Type: Electronic Ballast
 Standard Voltage: Universal 120- 277
 Options: Dimming Ballast, Emergency Ballast, Dual Cable Kit, With Lamps, Wireguard, Joiner
 Mounting: Cable, Chain or Pendant (**Mounting Hardware is Sold Separately**)
 Additional Info.: UL Listed & Title 24 Compliant

Catalog Ordering: Example: 5848-232-DIM-WL


58				
-----------	--	--	--	--

Catalog No.	Type:
Job Name:	

Specifications & Features:

A modern direct/indirect fixture in a bright white finish and perforated baffle with white opal acrylic inlay for attractive glare free lighting in offices, conference rooms, reception areas and classrooms.

- Housing made from die formed heavy-gauge pre-painted cold rolled steel
- Baffle is made of cold rolled steel with 5/64" diameter micro-perforations at staggered 7/64" intervals
- Hinged baffle for quick easy lamp access
- Diffuser is made of .020 white opal acrylic
- End-caps are molded white plastic
- Finished in a white polyester polymer with a minimum of 82% reflectivity
- Available in a variety of lamp configurations
- Suitable for damp location
- Optional Joiner assembly for continuous runs and tandem configurations
- Dual Cable Kit option available (**Mounting Hardware is Sold Separately**)



FAMILY TYPE	LENGTH IN INCHES/ LAMPING	# OF BALLASTS	BALLAST/ VOLTAGE	OPTIONS
58	48-132 (1- F32T8)	/1	UNV (120-277 Volt) DIM (Dimming Ballast)	EMR (450 Lumen Emergency Ballast) EMR 1400 (1400 Lumen Emergency Ballast) DC (Dual Cable) WL (With Lamps) JNR (Joiner)
	48-232 (2- F32T8)	/2		
	48-332 (3- F32T8)			
	96-132T (2- F32T8)			
	96-232T (4- F32T8)			
	96-332T (6- F32T8)			
	48-128 (1- F28T5)			
	48-228 (2- F28T5)			
	48-328 (3- F28T5)			
	48-154 (1- F54T5HO)			
	48-254 (2- F54T5HO)			
	48-354 (3- F54T5HO)			
	96-128T (2- F28T8)			
	96-228T (4- F28T5)			
	96-328T (6- F28T5)			
	96-154T (2- F54T5HO)			
	96-254T (4- F54T5HO)			
	96-354T (6- F54T5HO)			

Specifications and Dimensions Subject to change without notice

FSC Lighting 9120 Center Avenue, Rancho Cucamonga, CA 91730 Ph 909-948-8878 Fax 909-948-8510